

USB Extender

DIGITUS®

Part Number	DA-70141	DA-70139-2	DA-73120	DA-73121	DA-73122
Name	USB CAT Extender, USB 2.0	USB CAT Extender, USB 1.1	USB CAT Extender, USB 2.0, 150m	USB CAT Extender, USB 3.2 Gen1, 100m	USB Fiber Extender, USB 3.2 Gen1, 300m
Max. Range	50m	50m	150m (CAT 6/7), 100m (CAT 5e)	100m (CAT 6A/7), 50m (CAT 5e/6)	300m (LC multi-mode)
Cascading	✗	✗	Yes - Up to 300m by network switch	✗	✗
USB-A Ports	1	1	4	3	3
USB-C Port	✗	✗	✗	1	1
Cable Types	Cat 5/5e/6	Cat 5/5e/6/7	Cat 5e/6/7	Cat 5/5e/6/7	LC multi-mode OM3
USB Version	USB 2.0 (480 Mbps)	USB 1.1	USB 2.0 (480 Mbps)	USB 3.2 Gen1 (5 Gbps)	USB 3.2 Gen1 (5 Gbps)
Special Features	Plug & Play no drivers required power via USB & DC3.5 easy installation	Plug & Play no drivers required power via USB easy installation	Plug & Play no drivers required power supply via USB easy installation	Plug & Play no drivers required power supply via USB easy installation	Plug & Play no drivers required power supply via USB easy installation
Compatible OS	Windows, macOS, Linux	Windows, macOS, Linux	Windows, macOS, Linux, Android	Windows, macOS, Linux, iOS, iPadOS, Android	Windows, macOS, Linux, Android
Transmitter Interface	USB-A	USB-A	USB-A	USB-C	USB-A
Power Supply (Tx)	USB-powered	USB-powered	USB-powered	USB-powered	USB-powered
Power Supply (Rx)	DC 5V/1A	DC 5V/1A	DC 5V/1A	DC 12V/3A	DC 12V/2A
Receiver Ports	1 x USB-A	1 x USB-A	4 x USB-A	3 x USB-A, 1 x USB-C	3 x USB-A, 1 x USB-C
Housing	ABS	ABS	Metal	Metal	Metal
Hot-Plug	✓	✓	✓	✓	✓
Operating Temperature	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
Link to product	Link	Link	Link	Link	Link